

# SOUNDCOMMANDER®

<b>SC3500/3600/3660 Systems Specifications</b>			
	<b>SC3500</b>	<b>SC3600</b>	<b>SC3660</b>
<b>Power Amplifier Output</b>	360 Watts RMS Standard, 720 Dual System Watts Available		
<b>Inputs</b>	2 Wired, Mic-Aux, 2 Wireless, UHF & VHF		
<b>Audio Power Output. (RMS) Continuous</b>	130dB @ 1m	147dB @ 1m	147dB @ 1m
<b>Harmonic Distortion</b>	Less than 1% at full RMS Power		
<b>Max Range</b>	To 800m Dia 360°	To 2000m Directional	To 2000m Directional
<b>Speaker Interconnect Cable 3600/3660</b>	3'(1m) & 20' (6m) 14AWG Heavy Duty		
<b>Loudspeaker Cables</b>	1 Ea. 100' (30m)	2 Ea. 50' (15m)	2 Ea. 100' (30m)
<b>Loudspeakers</b>	6-Sprk 360° Array	6 Speakers (2 Arrays)	6 Speakers (2 Arrays)
<b>Speaker Frequency Response</b>	400 - 6500 Hz		
<b>Speaker Array Weight</b>	32 lbs (10 Kg)	17 lbs. (7.7 Kg) Each Array	
<b>Speaker Array Size</b>	24" X 7" Mounted	20" (508mm) X 11" (275mm) X 8" (200mm)	
<b>Batteries</b>	Two 12V 7.5 Ahr Rechargeable		
<b>AC Power Supply</b>	Switchable 115 or 230 VAC, 6 Amp in, 25 Amp Output		
<b>Case Material</b>	Polyethylene Plastic	Impact Resistant Rotationally Molded Plastic	
<b>Dimensions SC3600/3660 Speaker Arrays</b>	21 1/8" (537mm) X 13" (330mm) X 9" (229mm) 17lb (7.8Kg)		
<b>Array and Hard Case Combined</b>	72lb (32.7Kg)	37lb (16.8Kg)	37lb (16.8Kg)
<b>Available Colors</b>	Blue and Sand Mounts	Grey, Olive Drab Green, Black	
<b>Operating Climate</b>	-30° F (-34°C) to +140° F (60°C)		
<b>Power Cable</b>	7' (2.3m) 14AWG Heavy Duty		
<b>System Operational Weight W/ Cases</b>	118lb (53.6kg)	107lbs. (48.6Kg)	114lb (51.8Kg)
<b>Transport/Storage Weight</b>	152lbs. (69Kg)	120lbs. (54.5 Kg)	136lbs (63.6 Kg)
<b>Dimensions SC3000 Series Amp</b>	22" (56cm) X 12" (31cm) X 8" (20cm), 35lbs		
<b>Dimensions SC3500 Speaker Array</b>	23" (584mm) X 8" (200mm) X .25" (65mm), 32lbs (14.5Kg)		
<b>Dimensions SC3600/3660 (2 Cases Stacked)</b>	23" (580mm) X 32" (810mm) X 14" (310mm), 37lbs (16.8Kg) Ea Case.		
<b>Specifications subject to change without notice</b>			