



Jawless Immobilizers

APPLICATION/USE: Proven **Heavy Duty** unattended, on/off-street, municipal, campus, private, corporate and anti-theft/terrorism applications.

FEATURES MITI'S UNIQUE PATENTED RHINO "HOOK-LOC WITH GRABBER"

Domed HG Series "Hook-Loc with Grabber" models feature one-piece unitized construction, are light in weight and install in 15-30 seconds. No assembly required. The proven Rhino **HG** Series features the latest technology in immobilizer attachment systems. The reinforced design eliminates the possibility of damage, scratching or marring of the vehicle's wheel rim edge (flange). It deters forcible removal even if the tire is deflated. The **"Hook-Loc with Grabber"** attachment system is found only on Rhino Immobilizers.

- 1 Attachment by means of wheel rim edges (flanges) through attachment jaws is totally eliminated with the Rhino **HG** series immobilizers. The inner **"Hook-Loc"** arm indexes quickly within the inner wheel's cavity between the backing plate or drum, and the grabber (affixed to outer arm) indents into the sidewall of the tire, deterring movement.
- 2 Assist spring aids in installation of the immobilizer by holding the inner **"Hook-Loc"** arm against the inner wheel, where it is indexed between the wheel and brake backing plate.
- 3 Spring-loaded grabber provides superior resistance for preventing side-to-side movement and deterring forcible removal or drive-away.
- 4 Bi-directional stand design allows the immobilizer to be attached to any vehicle wheel - front, rear, left or right side. Unique to Rhino.
- 5 Each unit shipped with a Secur-Key and package of immobilization tags.

DOMED HG SERIES

6 Telescoping dome assembly with protective beading prevents removal of the wheel.

7 Baked-on environmentally safe safety orange powder coating provides high visibility and superior rust protection.

8 Deep dish dome provides space for protruding hubs. Prevents access to lug nuts.

9 MITI Rhino's stainless steel Secur-Bolt-Key system provides secure immobilizer attachment by means of a hardened steel-plated 3/4" custom machined bolt with 3/4" stainless steel welded nut, encapsulated in a 1 1/2" welded steel tube with 1/2" holes provided for optional padlock (recommended) and padlock cover, providing a three-tier high security locking system. When tightened, the secur-bolt applies pressure against the outer end of the inner pivotal arm, rotating it inward until the arm indexes into the wheel's cavity. Then the inward pressure is reversed at the stop, driving outer affixed and telescoping dome assembly against the outer wheel for a positive vice-like attachment.

DOMED HG SERIES MODELS "GRABBER"

FITS USA, foreign, subcompact to full size, light trucks, with std wheels & tires.

DOMED WHEEL COVERS 10"(25.40cm) 12"(30.48cm) 14"(35.35cm) 15"(40.24cm)

HG-10 WHEEL/TIRE 2 to 12" (5.08 - 30.48cm) WIDE X 12 to 16 1/2" (30.48 - 41.91cm) DIAMETER

UNIT SIZE 13 3/4" (33.66cm) (WIDTH) X 3 1/2" (80.01cm) (HEIGHT) X 10" (25.40cm) (DEPTH) 23 1/2 lbs (10.55kg) (WEIGHT)

PACKAGED 1 PER BOX 13" (33.02cm) X 3 1/2" (80.01cm) X 12" (30.48cm) 30 lbs (13.61kg)

PACKAGED 2 PER BOX 13" (33.02cm) X 3 1/2" (80.01cm) X 12" (30.48cm) 53 lbs (24.04kg)

HG-12 WHEEL/TIRE 2 to 12" (5.08 - 30.48cm) WIDE X 12 to 16 1/2" (30.48 - 41.91cm) DIAMETER

UNIT SIZE 13 3/4" (33.66cm) (WIDTH) X 3 1/2" (80.01cm) (HEIGHT) X 12" (30.48cm) (DEPTH) 24 1/2 lbs (11.11kg) (WEIGHT)

PACKAGED 1 PER BOX 13" (33.02cm) X 3 1/2" (80.01cm) X 12" (30.48cm) 27 lbs (12.25kg)

PACKAGED 2 PER BOX 13" (33.02cm) X 3 1/2" (80.01cm) X 12" (30.48cm) 56 lbs (25.40kg)

HG-14 WHEEL/TIRE 2 to 12" (5.08 - 30.48cm) WIDE X 12 to 16 1/2" (30.48 - 41.91cm) DIAMETER

UNIT SIZE 13 3/4" (33.66cm) (WIDTH) X 3 5/8" (82.55cm) (HEIGHT) X 14" (35.35cm) (DEPTH) 25 1/2 lbs (11.45kg) (WEIGHT)

PACKAGED 1 PER BOX 13" (33.02cm) X 3 1/2" (80.01cm) X 12" (30.48cm) 32 lbs (14.51kg)

PACKAGED 2 PER BOX 13" (33.02cm) X 3 1/2" (80.01cm) X 15" (38.10cm) 57 lbs (25.85kg)

HG-15 WHEEL/TIRE 2 to 17 1/2" (5.08 - 44.45cm) WIDE X 12 to 24" (30.48 - 60.96cm) DIAMETER

UNIT SIZE 13 3/4" (33.66cm) (WIDTH) X 3 5/8" (82.55cm) (HEIGHT) X 16" (40.64cm) (DEPTH) 26 1/2 lbs (11.91kg) (WEIGHT)

PACKAGED 1 PER BOX 13" (33.02cm) X 3 1/2" (80.01cm) X 12" (30.48cm) 29 lbs (13.15kg)

PACKAGED 2 PER BOX 13" (33.02cm) X 3 1/2" (80.01cm) X 15" (38.10cm) 61 lbs (27.67kg)

NOTE: 14/15" domed wheel covers are ideal for large diameter wheels, 12" are best for general use on all diameters, and 10" are ideal for extremely small diameter wheels. 15" are primarily used for municipal applications. **CAUTION:** The HG Grabber immobilizer is specifically designed to prevent/discourage unauthorized movement of the vehicle and may cause tire deflation or damage if vehicle is moved.

US PATENTS 6,032,497 / 5,865,048

ORDER FORM - PAGE 15 -



Immobilize to Collect Unpaid Violations.



