

# SoundCommander® Solar and Battery Backup System 600 Watt Hour

Solar Panel, Controller, and Batteries



## SoundCommander® Solar and Battery Backup System

The IML Corp 600Watt Hour Solar and Battery Backup System is the reliable way to ensure you have backup power when you need it most. This system includes a 50 watt eclipse solar panel, 20 amp PWM charge controller with 5v USB port, and two 12VDC 26Ah sealed lead acid storage batteries. With a 12V DC output of up to 20 amps, this system is perfect for powering your essential devices in an emergency situation. The ruggedized water resistant carrying case ensures that your system will be protected from the elements, making it the perfect choice for any applications where reliable backup power is a must.

The 100 Watt Eclipse Solar Panel system combines power and functionality to create an effortlessly sleek unit. The two 50W Monocrystalline Solar Panels come with one 15in set of wires with MC4 connectors. These solar panels are crafted with the highest efficiency cells, making them both smaller and lighter than its traditional counterpart. Weighing in at a mere 19.40 pounds, the Eclipse panels are also easier to transport and store. The built-in kickstand allows you to tilt the panel for greater sun coverage and charging efficiency. The complete SoundCommander® 600Watt Hour Solar and Battery Backup System weighs 55 lbs with the approximate dimensions of 18.5" x 13" x 10" (l x w x h).



## Two 50 Watt Eclipse Solar Panels

Reliable - Excellent performance in low-light environments, adjustable corrosion resistant aluminum stand, heavy duty handle and latches for longevity. Advanced encapsulation material with multi-layered sheet laminations to enhance cell performance and provide a long service life, EL tested solar modules; no hot-spot heating guaranteed, TPT back sheet ensures smooth performance over a long period of time.

Durable - Guaranteed positive output tolerance (0-3%); withstands high winds (2400Pa) and snow loads (5400Pa), Protective corners and corrosion-resistant aluminum frame for extended outdoor use, Anti-reflective, high transparency, low iron-tempered glass with enhanced stiffness and impact resistance, IP65 rated junction box provides complete protection against environmental particles and low-pressure water jets

Expandable - Designed for expansion, you can add panels to the the system based on your available space.

Maximum System Voltage: 600V DC (UL), Open-Circuit Voltage (Voc): 21.6V, Short-Circuit Current (Isc): 6.10A,

Maximum Power: 100W, Optimum Operating Voltage (Vmp): 17.6V, Panel Leads (Pair): 12AWG, IP65 Rated waterproof junction box, Optimum Operating Current (Imp): 2.73A, IP67 Rated waterproof MC4 connectors



The 600 Watt Hour Solar and Battery Backup System is fully ruggedized for field operations. It includes a 20 Amp PWM Charge Controller w/ 5v USB Port, Two 12VDC 26Ah Sealed Lead Acid Storage Batteries, 12V DC Output (Max 20 Amps), and is enclosed in a Ruggedized Water Resistant Carrying Case.

-  866-IML-CORP (465-2677), 1-678-331-3190
-  1-678-331-3170
-  sales@imlcorp.com
-  869 Pickens Industrial Dr. #15 Marietta Ga 30062 USA

SoundCommander® is manufactured in the USA by IMLCORP, LLC

